

| | | | | |
|---------------------------------------|-------------------------------------|---------|----------------------|---------------|
| ETH / 1 FLASH TYPICAL | Ex db IIB+H2 Gb Ex tb IIIC Db II2GD | | T5 T100°C | -20°C (-40°C) |
| | Ex db IIC Gb Ex tb IIIC Db II2GD | | | +60°C |
| COMBINATIONS LIGHT&SOUND HORN&LAMP | zone 1 | zone 2 | DIRECTIVE 2014/34/UE | -20°C (-40°C) |
| COMBINAZIONI OTTICO ACUSTICA | zone 2 | zone 22 | | +40°C |
| | | | IP66 | |

Caratteristiche: Esempi tipici di combinazione OTTICO&ACUSTICA a normativa ATEX con scatola morsettiera.

Features: Typical examples LIGHT&SOUND combinations a new standard ATEX with terminals box.

ETH / 1 FLASH

TIPICO 2 / TYPICAL 2
ETH20MD 4W + EVA50
+ JBOX



TIPICO 1 / TYPICAL 1
ETH20MD 4W + EVA50
+ JBOX

TIPICO 3 / TYPICAL 3
ETH20MD 10W + EVA50 + JBOX



TIPICO 4 / TYPICAL 4
1 ETH20MD 4W + 2 EVA50 + JBOX



TIPICO 5 / TYPICAL 5
1 ETH20MD 10W + 2 EVA50 + JBOX



TIPICO 6 / TYPICAL 6
1 ETH20MD 4W + 3 EVA50 + JBOX



TIPICO 7 / TYPICAL 7
1 ETH20MD 10W + 3 EVA50 + JBOX



Kroma mec S.r.l.

51



| | | | | |
|---------------------------------------|-------------------------------------|---------|----------------------|---------------|
| ETH / 2 FLASH TYPICAL | Ex db IIB+H2 Gb Ex tb IIIC Db II2GD | | T5 T100°C | -20°C (-40°C) |
| | Ex db IIC Gb Ex tb IIIC Db II2GD | | | +60°C |
| COMBINATIONS LIGHT&SOUND HORN&LAMP | zone 1 | zone 2 | DIRETTIVE 2014/34/UE | T6 T85°C |
| COMBINAZIONI OTTICO ACUSTICA | zone 2 | zone 22 | | -20°C (-40°C) |
| | | | IP66 | +40°C |

Caratteristiche: Esempi tipici di combinazione OTTICO-ACUSTICA a normativa ATEX con scatola morsettera.

Features: Typical examples LIGHT&SOUND combinations a new standard ATEX with terminals box.

ETH / 2 FLASH

TIPICO 1 / TYPICAL 1
1 ETH20MD 4W + 3 EVA50 + JBOX



TIPICO 2 / TYPICAL 2
1 ETH20MD 10W + 3 EVA50 + JBOX



TIPICO 3 / TYPICAL 3
1 ETH20MD 4W + 2 EVA50 + JBOX



TIPICO 4 / TYPICAL 4
1 ETH20MD 10W + 2 EVA50 + JBOX



TIPICO 5 / TYPICAL 5
1 ETH20MD 10W + 2 EVA + JBOX



TIPICO 6 / TYPICAL 6
1 ETH20MD 4W + 2 EVA + JBOX



Kroma mec S.r.l.

51



| | | | | |
|---------------------------------------|-------------------------------------|---------|--------------|---------------|
| ETH / 3 FLASH TYPICAL | Ex db IIB+H2 Gb Ex tb IIIC Db II2GD | | T5 T100°C | -20°C (-40°C) |
| | Ex db IIC Gb Ex tb IIIC Db II2GD | | | +60°C |
| COMBINATIONS LIGHT&SOUND HORN&LAMP | zone 1 | zone 2 | T6 T85°C | -20°C (-40°C) |
| COMBINAZIONI OTTICO ACUSTICA | zone 2 | zone 22 | | +40°C |

DIRECTIVE 2014/34/UE



IP66

Caratteristiche: Esempi tipici di combinazione OTTICO-ACUSTICA a normativa ATEX con scatola morsettiera.
Features: Typical examples LIGHT&SOUND combinations a new standard ATEX with terminals box.

ETH / 3 FLASH

TIPICO 1 / TYPICAL 1
1 ETH20MD 10W + 3 EVA50 + JBOX



TIPICO 2 / TYPICAL 2
1 ETH20MD 4W + 3 EVA50 + JBOX



TIPICO 3 / TYPICAL 3
2 ETH20MD 10W + 2 EVA50 + JBOX



TIPICO 4 / TYPICAL 4
1 ETH20MD 4W + JBOX SS Exe



TIPICO 5 / TYPICAL 5
1 ETH20MD 10W + 3 EVA50 + JBOX + PLATE



Kroma mec S.r.l.

